# **Hierarchical Task Network (HTN) Planning**

Section 12.2

#### **Outline**

- Example
- Primitive vs. non-primitive operators
- HTN planning algorithm
- Practical planners


Additional references used for the slides:

desJardins, M. (2001). CMSC 671 slides. www.cs.umbc.edu

# **Hierarchical Task Network (HTN) planning**

- Idea: Many tasks in real life already have a built-in hierarchical structure
- For example: a computational task, a military mission, an administrative task
- It would be a waste of time to construct plans from individual operators. Using the built-in hierarchy help escape from exponential explosion
- Running example: the activity of building a house consists of obtaining the necessary permits, finding a builder, constructing the exterior/interior, ...
- HTN approach: use abstract operators as well as primitive operators during plan generation.

# **Building a house**




# **Hierarchical decomposition**

- HTN is suitable for domains where tasks are naturally organized in a hierarchy.
- Uses abstract operators to start a plan.
- Use partial-order planning techniques and action decomposition to come up with the final plan
- The final plan contains only primitive operators.
- What is to be considered primitive is subjective: what an agent considers as primitive can be another agent's plans.


### Representing action decompositions

- A plan library contains both primitive and non-primitive actions.
- Non-primitive actions have external preconditions, as well as external effects.
- Sometimes useful to distinguish between *primary* effects and secondary effects.

### **Building a house with causal links**



# Another way of building a house



# **Example action descriptions**

Action(BuyLand, Precond: Money, Effect: Land △¬ Money)
Action(GetLoan, Precond: GoodCredit, Effect: Money △ Mortgage)
Action(BuildHouse, Precond: Land, Effect: House)

Action(GetPermit, Precond:Land, Effect: Permit)

Action(HireBuilder, Effect: Contract)

Action(Construct, Precond:Permit ∧ Contract,

Effect: *HouseBuilt* ∧¬ *Permit*)

Action(PayBuilder, Precond: Money ∧ HouseBuilt,

Effect: ¬ *Money* ∧ *House* ∧¬ *Contract*)

# **Example action descriptions**

```
Decompose(BuildHouse, Plan(STEPS:\{S_1: GetPermit, S_2: HireBuilder, S_3: Construction, S_4: PayBuilder, \} Orderings: \{Start \prec S_1 \prec S_2 \prec S_3 \prec S_4 \prec Finish, Start \prec S_2 \prec S_3 \}, Links: \{Start \ \underline{Land} \ S_1, Start \ \underline{Money} \ S_4, S_1 \ \underline{Permit} \ S_3, S_2 \ \underline{Contract} \ S_3, S_3 \ \underline{HouseBuilt} \ S_4, S_4 \ \underline{House} \ Finish, S_4 \ \underline{\neg Money} \ Finish\}))
```


#### Correctness

- A decomposition should be a correct implementation of the action.
- ▲ A plan d implements an action a correctly if d is a complete and consistent partial-order plan for the problem of achieving the effects of a given the preconditions of a (result of a sound POP).
- The plan library contains several decompositions for any high-level action.
- Each decomposition might have different preconditions and effects. The preconditions of the high-level action should be the intersection of the preconditions of the decompositions (similarly for the external effects.)

# **Information hiding**

- The high-level description hides all the *internal* effects of decompositions (e.g., Permit and Contract).
- It also hides the duration the internal preconditions and effects hold.
- Advantage: reduces complexity by hiding details
- Disadvantage: conflicts are hidden too


# **Example**



# For each decomposition d of an action a

- Remove the high level action, and insert/reuse actions for each action in d. reuse → subtask sharing
- Merge the ordering constraints (If there is an ordering constraint of the form  $B \prec a$ , should every step of d come after B?)
- Merge the causal links

# **Action ordering**



#### **HTN planners**

- Most industrial strength planners are HTN based.
- O-PLAN combines HTN planning with scheduling to develop production plans for Hitachi.
- SIPE-2 is an HTN planner with many advanced features
- SHOP is an HTN planner developed at the University of Maryland. It can deal with action durations.

#### The features of SIPE-2

- Plan critics
- Resource reasoning
- Constraint reasoning (complex numerical or symbolic variable and state constraints)
- Interleaved planning and execution
- Interactive plan development
- Sophisticated truth criterion
- Conditional effects
- Parallel interactions in partially ordered plans
- Replanning if failures occur during execution

# An operator with constraints

```
OPERATOR decompose
PURPOSE: Construction
CONSTRAINTS:
 Length (Frame) <= Length (Foundation),
 Strength (Foundation) > Wt(Frame) + Wt(Roof)
  + Wt(Walls) + Wt(Interior) + Wt(Contents)
PLOT: Build (Foundation)
 Build (Frame)
 PARALLEL
  Build (Roof)
  Build (Walls)
 END PARALLEL
 Build (Interior)
```

#### **More on SIPE-2**

- Russell & Norvig explicitly represent causal links; these can also be computed dynamically by using a model of preconditions and effects (this is what SIPE-2 does)
- Dynamically computing causal links means that actions from one operator can safely be interleaved with other operators, and subactions can safely be removed or replaced during plan repair
- Russell & Norvig's representation only includes variable bindings, but more generally we can introduce a wide array of variable constraints

#### **Truth Criterion**

- Determining whether a formula is true at a particular point in a partially ordered plan is, in the general case, NP-hard
- Intuition: there are exponentially many ways to linearize a partially ordered plan
- In the worst case, if there are N actions unordered with respect to each other, there are N! linearizations

#### **Truth Criterion**

- Ensuring soundness of the truth criterion requires checking the formula under all possible linearizations
- Use heuristic methods instead to make planning feasible
- Check later to be sure no constraints have been violated

# **Truth Criterion in Sipe-2**

- Heuristic: prove that there is one possible ordering of the actions that makes the formula true, but don't insert ordering links to enforce that order
- Such a proof is efficient
  - Suppose you have an action A1 with a precondition P
  - Find an action A2 that achieves P (A2 could be initial world state)
  - Make sure there is no action necessarily between A2 and A1 that negates P
- Applying this heuristic for all preconditions in the plan can result in infeasible plans

# **Comments on HTN planning**

- The major idea is to gain efficiency by using the library of preconstructed plans.
- When there is recursion, it is undecidable even if the underlying state space is finite.
  - recursion can be ruled out
  - the length of solutions can be bound
  - can use a hybrid POP and HTN approach

# **Comments on HTN planning (cont'd)**

Subtask sharing is nice, but it takes time/resources to notice the opportunities

Would interprocedural optimization be a possibility? Consider tan(x) - sin(x). Both have Taylor series approximations:

$$tan(x) \approx x + \frac{x^3}{3} + \frac{2x^5}{15} + \frac{17x^7}{315}$$
$$sin(x) \approx x - \frac{x^3}{6} + \frac{x^5}{120} - \frac{x^7}{5040}$$

It would be nice to share terms but a compiler can only optimize within the code because it does not have the source; and if it did interprocedural optimization tan and sin would always have to be changed together.

# **Comments on HTN planning (cont'd)**

- Suppose that we want to construct a plan with n actions
  - Forward state space planning takes  $O(b^n)$  with b allowable actions at each state.
  - HTN planning can construct  $d^{(n-1)/(k-1)}$  decomposition trees with d possible decompositions with k actions each
    - $\rightarrow$  keeping d small and k large can result in huge savings (long macros usable across a wide range of problems)
  - HTN-based planners do not address uncertainty